

# Product information

## megol Premium Getriebeoel HC GL 4 SAE 75W-80



### Description

Gearbox oil based on HC synthetic technology which is suitable for use in manual transmissions especially those with retarders/intarders, mechanical non-synchronized transmissions, steering systems and auxiliary transmissions. megol Premium Getriebeoel HC GL 4 SAE 75W-80 can be used in commercial vehicles – even for extended oil change intervals up to 320,000 km – and in passenger cars. It can also be used in cases where difficulties arise in shifting gears using single-grade oils/higher viscosity API GL 4 products, for example.

The instructions issued by the manufacturers are to be followed!

### Approvals

API GL4 • MAN 341 Typ Z4 • ZF TE-ML 02L • ZF TE-ML 16K • ZF approval number ZF000394

### Meguin also recommends this product for vehicles that are subject to the following specifications

DAF • Eaton Extended Drain (300.000 km) • IVECO • MAN 341 Typ E3 • Renault Trucks • Volvo 97305 • ZF TE-ML 08

### Characteristic data

SAE class (gear oils)	75W-80 SAE J306
Density at 15 °C	0,86 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	55,8 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	9,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	154 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	240 °C DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049

### Available pack sizes

20 l Canister plastic	6841 D-GB
200 l Drum sheet metal	6843 D-GB