

Product information

megol Motorenoel Premium Performance SAE 0W-20



Description

Premium motor oil with outstanding performance. Produced on the basis of the best raw materials and the very latest technologies. Provides excellent lubricating film, aging and shear stability, optimum wear protection and maximum engine cleanliness. Ensures perfect engine running under all temperature and operating conditions and enables the reduction of fuel consumption.

Specifications / Approvals

ACEA C5 • ACEA C6 • API SP • ILSAC GF-6A • BMW Longlife-17 FE+ • MB-Approval 229.71 • MB-Approval 229.72 • Opel OV 040 1547 - A20

Meguin also recommends this product for vehicles that are subject to the following specifications

Chrysler MS-12145 • Fiat 9.55535-GSX • Ford WSS-M2C 947-B1 • Ford WSS-M2C 962-A1 • Jaguar / Land Rover STJLR.03.5006

Characteristic data

SAE class (engine oils)	0W-20 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	43 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8,5 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	180 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D 5481
Pour point	-48 °C DIN ISO 3016
Evaporation loss (Noack)	11 % CEC-L-10-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,3 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 % DIN 51575

Characteristic data

Color number (ASTM)	L 3,0
	DIN ISO 2049

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed! Optimum effectiveness is only possible when the product is used unmixed.

Available pack sizes

1 l Canister plastic	33068 D-GB-F-ARAB-RUS-GR-I-E-P
4 l Canister plastic	33073 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	33069 D-GB-F-ARAB-RUS-GR-I-E-P
20 l Canister plastic	33070 D-GB
60 l Black plate barrel	33071 D-GB
200 l Black plate barrel	33072 D-GB