

Product information

megol Motorenoel Syntech Premium SAE 10W-40



Description

Low-friction motor oil for year-round use in gasoline and diesel engines with and without turbocharging. Thanks to its optimum combination of base oils and additive technology, improves the engine performance and reduces friction and wear. Ideal for use in older vehicles (youngtimers).

Range of applications: Passenger cars.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA A3 • ACEA B4 • API SN • API CF • MB-Approval 229.3 • VW 501 01 • VW 505 00

Meguin also recommends this product for vehicles that are subject to the following specifications

MB 229.1 • Peugeot Citroen (PSA) B71 2300

Characteristic data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,87 g/cm ³ DIN 51757
Viscosity at 40 °C	95,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14 mm ² /s ASTM D 7042-04
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	≤ 7000 mPas ASTM D5293
Viscosity index	150 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	12 % CEC-L-40-A-93
Flash point	232 °C DIN ISO 2592
Total base number	10,8 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575

Characteristic data

Color number (ASTM) 2,5
DIN ISO 2049

Available pack sizes

1 l Canister plastic	4339 D-GB-F-ARAB-RUS-RO-I-E-P
1 l Canister plastic	9600 GB-F-E-P-NL-ARAB
4 l Canister plastic	6475 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	4338 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	9601 GB-F-E-P-NL-ARAB
20 l Canister plastic	4797 D-GB
60 l Black plate barrel	4798 D-GB
200 l Black plate barrel	4799 D-GB
1.000 l Container	6884 D-GB
1.000 l Deposit container	9733 D-GB
1 l Bulk goods	4680 D