

Product information

megol Motorenoel Super Leichtlauf 5W-50



Description

Modern, fully synthetic low-friction motor oil for year-round use. Motor oil with low viscosity and high shear stability thanks to synthetic base oils and innovative additive technology. This product reliably prevents the formation of deposits, reduces frictional losses in the engine and optimally protects against wear. This results in fuel savings and extended service life of the engine. Recommended for gasoline and diesel engines, including those with a turbocharger and catalytic converter.

Available pack sizes

4 l Canister plastic 33002
GB-F-E-P-NL-ARAB

Note the manufacturer's instructions!

Approvals

ACEA A3 • ACEA B4 • API SN • API CF

Meguin also recommends this product for vehicles that are subject to the following specifications

BMW Longlife-98 • MB 229.3 • Porsche A40 • VW 502 00 • VW 505 00

Characteristic data

Viscosity	5W-50
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	122 mm ² /s DIN 51562
Viscosity at 100 °C	18,7 mm ² /s DIN 51562
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D5293
Viscosity index	172 DIN ISO 2909
HTHS at 150°C	>=3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	7,4 % CEC-L-40-A-93
Flash point	240 °C DIN ISO 2592
Total base number	10,5 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L3,5 DIN ISO 2049