

Product information

megol Zentralhydraulikoel



Description

Special, synthetic and mineral oil-based hydraulic oil with ash-free additives to improve its viscosity, coefficient of friction, wear protection, oxidation protection, foaming and corrosion protection properties. It offers an ideal capacity for use as a central hydraulic oil in power steering and level control systems, hydraulic brake boosters and hydropneumatic suspension systems. megol central hydraulic oil's special formulation guarantees an excellent cold behaviour and is therefore particularly suited for use in cold countries. The instructions issued by the manufacturers are to be followed.



Approvals

MAN 3289

Meguin also recommends this product for vehicles that are subject to the following specifications

BMW 81 22 9 407 758 • Ford WSS-M2C 204-A • MB 345.0 • Opel 1940 766 • VW G 004 000 • VW G 002 000
• ZF TE-ML 02K

Characteristic data

Viscosity at 40 °C	19,6 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	6,4 mm ² /s ASTM D 7042-04
Viscosity index	322 DIN ISO 2909
Color / appearance	green
Density at 15 °C	0,825 g/cm ³ DIN 51757
Flash point	150 °C DIN ISO 2592
Pour point	-72 °C DIN ISO 3016
Foaming behavior at 24 °C	50/0 ml ISO 6247
Foaming behavior at 93.5 °C	35/0 ml ISO 6247

Available pack sizes

1 l Canister plastic	6304 D
20 l Canister plastic	8641 D-GB